




FLEXIBLE ENGINEERING SOLUTIONS



INDUSTRIAL HOSES

ABRASIVE MATERIAL DELIVERY



APPLICATION	Abrasive Material Delivery hose suitable for the discharge of dry bulk cement from tankers.
TUBE	Black SBR Blend
COVER	Black SBR Blend
REINFORCEMENT	Textile Braid
TEMPERATURE	-30°C to +80°C (-22°F to +176°F)

HOSE SPECIFICATIONS FOR ABRASIVE MATERIAL DELIVERY HOSE

Part No.	ID		OD mm	Working Pressure		Min. Burst Pressure		Bend Radius mm	Weight kg/m
	inch	mm		bar	psi	bar	psi		
26-MD1075	3	76.2	89.0	10	150	30	450	610	2.12
26-MD1100	4	101.2	117.0	10	150	30	450	815	3.37
26-MD1125	5	127.0	145.0	10	150	30	450	1015	4.92

WA

Midvale
49 Farrall Road
Midvale WA 6056
p: +61 8 6274 9333

Canning Vale
27B Baile Road
Canning Vale WA 6155
p: +61 8 9235 7500

Welshpool
Unit 11, 64 Kewdale Road
Welshpool WA 6106
p: +61 8 9251 2255

NT

Darwin
18 Callanan Road
Yarrowonga NT 0830
p: +61 8 8936 7698

QLD

Brisbane
51 Robinson Road East
Virginia QLD 4014
p: +61 7 3868 1656