



CHEMICAL SUCTION & DELIVERY



APPLICATION	Suitable for the suction and discharge of a wide variety of industrial chemicals. Corrugated cover for additional flexibility.
TUBE	UHMWPE
COVER	Corrugated Blue EPDM Blend *4' & 6" sizes are standard cover
REINFORCEMENT	Spiral-plyed Synthetic Fabric with Dual Wire Helix
TEMPERATURE	-40°C to +93°C (-40°F to +199°F)
APPLICABLE STANDARDS	Meets or exceeds the requirements of AS 2594:1983

HOSE SPECIFICATIONS FOR CHEMICAL SUCTION & DELIVERY HOSE

Part No.	ID		OD mm	Working Pressure		Min. Burst Pressure		Bend Radius mm	Weight kg/m
	inch	mm		bar	psi	bar	psi		
27-CHEM2025	1	25.4	37.8	20	300	80	1200	90	1.04
27-CHEM2032	1-1/4	31.8	44.2	20	300	80	1200	110	1.28
27-CHEM2038	1-1/2	38.1	50.9	20	300	80	1200	135	1.54
27-CHEM2050	2	50.8	64.8	20	300	80	1200	180	2.26
27-CHEM2063	2-1/2	63.5	79.9	20	300	80	1200	220	3.14
27-CHEM2075	3	76.2	95.4	20	300	80	1200	265	4.55
27-CHEM2100*	4	101.6	122.0	20	300	80	1200	355	6.35
27-CHEM2150*	6	152.4	178.8	20	300	80	1200	685	12.29

WA

Midvale
49 Farrall Road
Midvale WA 6056
p: +61 8 6274 9333

Canning Vale
27B Baile Road
Canning Vale WA 6155
p: +61 8 9235 7500

Welshpool
Unit 11, 64 Kewdale Road
Welshpool WA 6106
p: +61 8 9251 2255

NT

Darwin
18 Callanan Road
Yarrowonga NT 0830
p: +61 8 8936 7698

QLD

Brisbane
51 Robinson Road East
Virginia QLD 4014
p: +61 7 3868 1656